

# Door Strike Intermediate Relay Module

# 011269



## Parts List

- (1) Door Strike Intermediate Relay Module
- (1) Accessory kit
- (2) Cable Clamps

## Specifications


Power Input	9 to 250 VAC or 5 to 60 VDC
Operating temperature	-10° C to 50° C (14° F to 122° F)
Relay Voltage/Current	12 A @ 250 VAC / 12 A @ 24 VDC
Maximum distance from Device	50 feet



## Warning

*Electrical Hazard:* Hazardous voltages may be present. No user serviceable part inside. Refer to qualified service personnel for connecting or servicing.


## Dimensions




## Assembly

### Tools required for assembly:


- A 3.17-mm (1/8-inch) flat blade screwdriver for the terminal block screws
- A size 1 Phillips screwdriver for the Door Strike Relay Module Cover Screws



## Connections



## Typical Wiring



## Contacting CyberData

### Corporate Headquarters

CyberData Corporation  
3 Justin Court  
Monterey, CA 93940, USA

Phone: 831-373-2601  
Fax: 831-373-4193  
www.CyberData.net

Sales: (831) 373-2601 ext. 334  
Support: 831-373-2601 ext. 333  
Web: <http://www.cyberdata.net/support/contactsupportvoip.php>  
RMA Dept: (831) 373-2601 ext. 136  
Email: [RMA@CyberData.net](mailto:RMA@CyberData.net)  
RMA Status: <http://www.cyberdata.net/support/rmastatus.html>

Warranty information is available at:  
Web: <http://www.cyberdata.net/support/warranty/index.html>