

Secure Access Control Keypad

The CyberData Secure Access Control Keypad uses the existing VoIP network infrastructure to securely unlock and lock gates or doors.

PoE-powered and in a secure outdoor-rated case, this VoIP Security Endpoint can store up to 500 access codes. There is a blacklisted code list that when activated, will make a phone call and play a pre-recorded message or can broadcast a multicast message to IP notification endpoints. Good code and blacklisted code lists can be updated on the web interface or autoprovisioned by a remote server.



Features

- SIP compliant
- PoE 802.3af enabled (Powered-over-Ethernet)
- IP 65 outdoor-rated
- Optional weather shroud for even greater weather protection
- Alert buzzer
- Red/Green lock status lights
- Can operate in standalone mode. PBX not required. Future-proof and adaptable when upgrading to new VoIP PBX
- Built in time of access scheduler
- Local and remote logging with time stamp
- NTP time support
- Network web management
- Supports 500 Access Codes
- Blacklisted code alert via dialout and multicast stored message
- Network downloadable firmware
- Dry contact relay to trigger door lock or unlock gates
- Door closure and tamper alert signal
- Support for CyberData's Networked Dual Door Strike Relay (Part# 011375) and Intermediate Door Strike Relay (Part# 011269)
- Security Torx screws with driver kit included

Specifications

Ethernet I/F	10/100 Mbps
Protocol	SIP RFC 3261 Compatible
Power Input	PoE 802.3af compliant or +8 to +12VDC @ 1000mA Regulated Power Supply
On-Board Relay	1A at 30 VDC
Operating Range	Temperature: -40°C to 55°C (-40° F to 131° F) Humidity: 5-95%, non-condensing
Storage Temperature	Temperature: -40° C to 70° C (-40° F to 158° F)
Storage Altitude	Up to 15,000 ft. (4573 m)
IP Rating	IP65
Dimensions	5.118 inches [130 mm] Length 2.252 inches [57.21 mm] Width 5.118 inches [130 mm] Height
Weight	2.0 lbs. (0.90 kg)
Boxed Weight	3.0 lbs. (1.36 kg)
Compliance	CE; EMC Directive – Class A EN 55032 & EN 55024, LV Safety Directive – EN 60950-1, RoHS Compliant, FCC; Part 15 Class A, Industry Canada; ICES-3 Class A, IEEE 802.3 Compliant
Warranty	2 years limited
Part Number	011433 011188 Weather Shroud (sold separately)

The following products are also available (sold separately):



Outdoor Intercom Shroud
#011188



Network Dual Door Strike Relay
#011375



Door Strike Relay Module
#011269



Auxiliary RGB Strobe
#011288

Secure Access Control Keypad

Typical Installation (Door Strike Options)

